

Bluetooth Combo Printer Adapter

– Class1

ACT-BT5800UB

- Supports Bluetooth Hard Copy Replacement Printing Profile (HCRP) .
- Supports Bluetooth Serial Port Profile (SPP)
- Supports Bluetooth v2.0 + EDR .
- Operates in 2.4 GHz~2.483 GHz ISM band .
- Bluetooth Class 1 .
- Operating distance up to 100 meters
- Supports both USB (serial) and Centronic (parallel) printer port interfaces .
- 256 bytes outbound buffer and 256 bytes inbound buffer.
- LED indicating: Power On/Off; Printer Action; Bluetooth Link
- Easy operation and setup .
- Size : 76(L) x 62(W) x 20(H) mm

All trademarks, logos, organization & company names and product model names are the properties of their respective owners.



Bluetooth Combo Printer Adapter

ACT-BT5800UB

Specifications

- **Frequency Band :**
2.4 - 2.483 GHz
- **Standard :**
Bluetooth v2.0 + EDR
- **Spread Spectrum :**
FHSS
- **Services Supported :**
SPP & HCRP
- **Sensitivity:**
< -88dBm at < 0.1% BER
- **Power & Consumption :**
Input 5V DC; Consumption: Tx Typical 115 mA, Rx Typical 75 mA, Standby 15mA
- **Working Distance:**
100 Meters
- **I/O Interface:**
USB & IEEE-1284
- **Certifications:**
CE, FCC, BQB
- **Humidity:**
5 ~ 90% non-condensing
- **Operating Temperature / Storage Temperature :**
0°C to 60 °C / -10°C to 70°C

All trademarks, logos, organization & company names and product model names are the properties of their respective owners.

 **ACTiSYS** Corporation

921 Corporate Way, Fremont, CA 94539

Tel: +1-510-490-8024, Fax: +1-510-623-7268

E-mail: irda-info@actisys.com, <http://www.actisys.com>

