

IrDA[®] Compliant Protocol Processor

ACT-IR8250P

- A complete IrDA[®] Protocol stack in a single chip, including mandatory protocols (IrPHY[™], IrLAP[™], IrLMP[™]) and optional protocols (IrLPT[™], IrCOMM[™]+TinyTP[™], OBEX transport or TinyTP with customized IAS[™] class name for IrSocket).
- Also includes IrPHY[™] encoding/decoding, and interfaces directly to Infrared transceivers for data rate from 9.6kbps up to 115.2 kbps. Only an external Infrared transceiver is needed to complete an IrDA compliant infrared communication subsystem.
- Supports IrDA[®] Secondary mode only.
- Supports 64 bytes data packet for IrDA[®] IrLAP[™] frame.
- Interfaces to Host device via a full function UART port.
- Supports host baud rate from 300k bps to 115.2k bps selecting by programmable settings.
- Programmable Device name, IAS[™] class name and data format setting.
- Available in programmed and tested chip (ACT-IR8250P), assembled & tested board (ACT-IR8250PDB), or assembled & tested evaluation kit (ACT-IR8250PEK).
- Low supply voltage, 3.0 V to 3.6 V.
- Low current consumption; 2 μ A standby, 3 mA active.
- Small low profile plastic 28-pin SSOP/TSSOP package.
- In-system-programmable FLASH, facilitates firmware changes or updates.
- The evaluation kit (ACT-IR8250PEK) includes AC power supply, RS232 level translators, and PC software for in-system re-programming of firmware and future firmware options.

All company and product names are the trademarks of the respective companies

